

1. A method of pattern recognition, said method comprising the steps of:

10 a second step for calculating feature-amount fB1i using the
feature-extracting-matrix BF with respect to typical pattern B1i of respective
classes "i" of the training pattern set B1;

15 a fourth step for determining an element, among the feature
amount fB_{li} retained in the referential database, most similar to a feature
amount fA_{2j} extracted from the matrix AF applied to input pattern A_{2j} ; *where does this come from?*

20 estimating between-class scatters $C_a - b$, $C_b - b$ of the
pattern sets A1, B1 and within-class scatter $C_a - w$ of the pattern set A1 from
the training pattern sets A1, B1;

calculating within-class scatter $C_{ab} - w$ and between-class
scatter $C_{ab} - b$, both extending over the pattern sets A1, B1, based on a set of
25 pair of elements corresponding to the pattern sets A1, B1; and

calculating a feature-extraction-function which maximizes $C_a - b$, $C_b - b$, and $C_{ab} - b$ out of the five statistical amounts, i.e., $C_a - b$, $C_b - b$,

$C_a - w$, $C_{ab} - w$, $C_{ab} - b$, and minimizes $C_a - w$, $C_{ab} - w$.

3. The method of pattern recognition of claim 1, wherein the pattern set A1 is obtained through shooting an object with a video camera, and
5 the pattern set B1 is obtained through taking an object with an image scanner.

4. The method of pattern recognition of claim 1, wherein the steps 1, 2 and 3 are done in off-line process and the step 4 is done in on-line process.

10 5. The method of pattern recognition of claim 3, wherein the pattern set A1 is formed by a plurality of images with respect to one object, and the pattern set B1 is formed by a single photo with respect to one object.

15 6. A method of pattern check, said method comprising the steps of:
a first step for finding feature-extraction-matrix AF of pattern set A1 and feature-extraction-matrix BF of pattern set B1, said matrices AF, BF maximizing between-class scatter and minimizing within-class scatter with respect to the training pattern sets A1, B1 ^{which are sets of pair of patterns} which are sets of pair of patterns obtained from a same object but on different conditions;

20 a second step for calculating feature amounts "fa", "fb" of input patterns "a", "b" using the matrices AF, BF ^{to compare}; and

a third step for determining whether or not the input patterns "a", "b" derive from a same class based on similarity measure of the feature amounts "fa", "fb".

25

7. The method of pattern check of claim 6, wherein the feature-extraction-matrices AF, BF are calculated through the steps of:

00074199-060501

estimating between-class scatters $C_a - b$, $C_b - b$ of the pattern sets A1, B1, which are sets of patterns obtained on different conditions, and within-class scatters $C_a - w$, $C_b - w$ of the pattern sets A1, B1;

calculating within-class scatter $C_{ab} - w$ and between-class
5 scatter $C_{ab} - b$, both extending over the pattern sets A1, B1, based on a set of pair of elements corresponding to the pattern sets A1, B1; and

calculating a feature-extraction-function which maximizes
10 $C_a - b$, $C_b - b$, and $C_{ab} - b$ out of the six statistical amounts, i.e., $C_a - b$, $C_b - b$, $C_a - w$, $C_b - w$, $C_{ab} - w$, $C_{ab} - b$, and minimizes $C_a - w$, $C_b - w$, $C_{ab} - w$.

8. The method of pattern recognition of claim 6, wherein the pattern set A1 is obtained through shooting an object with a video camera, and the pattern set B1 is obtained through taking an object with an image scanner.

15 9. The method of pattern recognition of claim 6, wherein the first step is done in off-line process and the second and third steps are done in on-line process.

20 10. The method of pattern recognition of claim 8, wherein the pattern set A1 is formed by a plurality of images with respect to one object, and the pattern set B1 is formed by a single photo with respect to one object.

11. A pattern recognition apparatus comprising:

25 (a) pattern input means for obtaining training-pattern-sets A1, B1, which are sets of pair of patterns, from a same object but on different conditions;

(b) a feature-extraction-matrix generating unit for finding

00874199-060501
T05090" 66T4/860

feature-extraction-matrix AF of the pattern set A1 and feature-extraction-matrix BF of the pattern set B1, both matrices AF, BF maximizing between-class scatter and minimizing within-class scatter with respect to the pattern sets A1, B1;

5 (c) a feature-amount calculating unit for calculating a feature amount fB_{li} using the feature-extraction-matrix BF with respect to typical pattern B_{li} of each class "i" of the training pattern set B1;

(d) transfer means for transferring a set $\{fB_{li}\}$ of the feature amount fB_{li} and the feature-extraction-matrix BF to referential database FB1;
10 and

(e) optimum matching determination means for selecting an element most similar to feature amount fA_{2j} from the database by applying the feature-extraction-matrix AF to pattern A_{2j} input, the feature amount fA_{2j} being extracted after applying the matrix AF to the pattern A_{2j} .

15

12. The pattern recognition apparatus of claim 11, wherein said feature-extraction-matrix generating unit including:

(b-1) an estimating unit for estimating between-class scatters $C_a - b$, $C_b - b$ in the pattern sets and within-class scatter $C_a - w$ of the
20 pattern set A1 from the pattern sets A1, B1;

(b-2) a scatter calculating unit for calculating within-class scatter $C_{ab} - w$ and between-class scatter $C_{ab} - b$, both scatters extending over the pattern sets A1, B1, from sets of a pair of elements corresponding to the pattern sets A1, B1; and

25 (b-3) a feature-extracting-function unit for calculating a feature-extracting-function which maximizes $C_a - b$, $C_b - b$, $C_{ab} - b$ out of five statistical amounts, i.e., $C_a - b$, $C_b - b$, $C_a - w$, $C_{ab} - w$, $C_{ab} - b$, and minimizes

FOI 5090 65742860

Ca - w, Cab - w.

13. The pattern recognition apparatus of claim 11, wherein the pattern set A1 is obtained through shooting an object with a video camera, and
5 the pattern set B1 is obtained through taking an object with an image scanner.

14. The pattern recognition apparatus of claim 13, wherein the pattern set A1 is formed by a plurality of images with respect to one object, and the pattern set B1 is formed by a single photo with respect to one object.

10

15. A pattern check apparatus comprising:

(a) a pattern inputting unit for obtaining training pattern sets A1, B1, which are sets of pair of patterns, from a same object but on different conditions;

15

(b) a feature-extraction-matrix generating unit for finding feature-extraction-matrix AF of the pattern set A1 and feature-extraction-matrix BF of the pattern set B1, both matrices AF, BF maximizing between-class scatter and minimizing within-class scatter with respect to the pattern sets A1, B1;

20

(c) a feature-extracting-unit for calculating respective feature amounts "fa", "fb" using the feature-extracting-matrices AF, BF from input pattern "a", "b" supplied from said pattern input unit;

(d) an identity determination unit for determine whether or not the input patterns "a", "b" are derived from the same class based on
25 similarity measure of the feature amounts "fa", "fb".

16. The pattern check apparatus of claim 15, wherein said feature-

00874199-060501
F05090-66F72860

extraction-matrix generating unit including:

(b-1) an estimating unit for estimating between-class scatters $C_a - b$, $C_b - b$ and within-class scatter $C_a - w$, $C_b - w$ from the pattern sets A1, B1 respectively;

5 (b-2) a scatter calculating unit for calculating within-class scatter $C_{ab} - w$ and between-class scatter $C_{ab} - b$, both scatters extending over the pattern sets A1, B1, from sets of a pair of elements corresponding to the pattern sets A1, B1; and

10 (b-3) a feature-extracting-function unit for calculating a feature-extracting-function which maximizes $C_a - b$, $C_b - b$, $C_{ab} - b$ out of six statistical amounts, i.e., $C_a - b$, $C_b - b$, $C_a - w$, $C_b - w$, $C_{ab} - w$, $C_{ab} - b$, and minimizes $C_a - w$, $C_{ab} - w$, $C_{ab} - w$.

15 17. The pattern check apparatus of claim 15, wherein the pattern set A1 is obtained through shooting an object with a video camera, and the pattern set B1 is obtained through taking an object with an image scanner.

20 18. The pattern check apparatus of claim 17, wherein the pattern set A1 is formed by a plurality of images with respect to one object, and the pattern set B1 is formed by a single photo with respect to one object.

19. A recording medium which records a program of recognizing a pattern by a computer, said program carrying out the processes of:

25 (a) a process for finding feature-extraction-matrix AF of pattern set A1 and feature-extraction-matrix BF of pattern set B1, said matrices AF, BF maximizing between-class scatter and minimizing within-class scatter with respect to the training pattern sets A1, B1 which are sets of pair of patterns

00874199-060501

obtained from a same object but on different conditions;

(b) a process for calculating feature amount "fB1i" using the feature-extracting-matrix BF with respect to typical pattern "B1i" of respective classes "i" of the training pattern set B1;

5 (c) a process for retaining a set {fB1i} of the feature amount fB1i and the matrices AF, BF in a referential database; and

(d) a process for determining an element, among the feature amount fB1i retained in the referential database, most similar to a feature amount fA2j extracted from the matrix AF applied to input pattern A2j.

10

20. A recording medium which records a program of checking a pattern by a computer, said program carrying out the processes of:

(a) a process for finding feature-extraction-matrix AF of pattern set A1 and feature-extraction-matrix BF of pattern set B1, the matrices
15 AF, BF maximizing between-class scatter and minimizing within-class scatter with respect to the training pattern sets A1, B1 which are sets of pair of patterns obtained from a same object but on different conditions;

(b) a process for calculating feature amounts "fa", "fb" of input patterns "a", "b" using the matrices AF, BF; and

20 (c) a process for determining whether or not the input patterns "a", "b" derive from a same class based on similarity measure of the feature amounts "fa", "fb".

09874199"060501